


# RZM350 Series



HOD UV System	RZM350-5	RZM350-8	RZMW350-7	RZMW350-11
Number of lamps	5	8	7	11
Unit length (mm/inch)	1635 / 64.4	1635.2 / 64.4	1635.2 / 64.4	1635.2 / 64.4
Unit chamber width at widest point (mm/inch)	1293 / 50.9	1293 / 50.9	1390 / 54.7	1390 / 54.7
Unit weight (kg/lb.)	451 / 994	451 / 994	550 / 1213	550 / 1213
Unit volume (liter/gallon)	197 / 52	197 / 52	231 / 61	231 / 61

## All Models

Standard pipe connection options	Flange DIN2576 DN350
Maximum water temperature – lamps on (°C / °F)	60° / 140°
Maximum water temperature – lamps off (°C / °F)	90° / 194°
Maximum ambient temperature (°C / °F)	45° / 113°
Maximum working pressure (bar/PSI)	7 / 102
Lamp sleeve material	High grade fused silica (quartz)
Housing material	Stainless steel 316L / Super duplex
Controller	Flat touch-screen user interface integrated with remote monitoring & control
Power supply enclosure	Electrical cabinet
Enclosure protection rating	IP54
Electricity requirements	200* / 380 / 400 / 440 / 480 / 600* VAC 3 phases 50/60 Hz

\* Transformer required.

Specifications subjected to change without notice.

All dimensions and weights for reference only; ICD drawing should be used for design purposes.